


# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 2437 Accredited to ISO/IEC 17025:2017	<b>Yadav Measurements Private Limited</b> Issue No: 030 Issue date: 03 July 2019	
	Post Box 169 Plot No. F-373 - 375 Riico Bhamashah Industrial Area Kaladwas Udaipur 313 003 India	Contact: Mr B. M. Vyas Tel: +91 294 265 0127 Fax: +91 294 265 0129 E-Mail: <a href="mailto:yadav.measurements@ymllabs.com">yadav.measurements@ymllabs.com</a> Website: <a href="http://www.yadavmeasurements.com">www.yadavmeasurements.com</a>
Testing performed at the above address only		

### Flexible Scope

The laboratory is accredited to ISO/IEC17025:2017 for testing activities in accordance with the standards listed in the schedule. This may also include tests on the same or similar product types against standards, or customer-specified methods that are not specifically listed in this Schedule, providing that:

- (1) The method or standard does not introduce new principles of measurement.
- (2) The method or standard does not require measurements to be made outside the parametric boundaries defined in this Schedule.

Information about flexible scopes of accreditation is available in UKAS document LAB39 and EA document EA-2/05.

### NOTES

The abbreviation IS refers to Indian Standards and the abbreviation CBIP refers to the Central Bureau of Irrigation and Power, Government of India.

Tests carried out to IS13779:1999 include Amendment 1 (October 2003), Amendment 2 (October 2004), Amendment 3 (December 2004) and Amendment 4 (June 2006), Amendment 5 (March 2015)

Tests carried out to IS14697:1999 include Amendment 1 (October 2003), Amendment 2 (October 2004) and Amendment 3 (December 2004), Amendment 4 (Dec.2014)

Tests carried out to IS13779:1999 and IS14697:1999 include the reaffirmation of those standards that were carried out in 2004.

Tests carried out to CBIP 88:February 2002 include Amendment 4 (2005).

Publication No. 304 is dated 2008 and is published by CBIP.

Publication No. 325 is Jan, 2015 and is published by CBIP.



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

#### DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<u>1.0 EMC Tests</u>	
Computers and Peripherals Domestic Appliances: Electrical Electrical/Electronic Components Electrical/Electronic Connectors Electrical/Electronic Products Electronic Products: Digital Electro-Mechanical Devices IT Equipment Luminaires Micro-electronic Circuits and Components Office Equipment: Electrical Printed Circuit Boards Electrical equipment for measurement, control and laboratory use Audio, Video and similar electronic apparatus Instruments: Indicating/ Recording Medical & Diagnostic Instruments  Measuring Instruments – Electrical measuring transducers  Flow/Gas meters	1.1 Conducted Radio interference Emissions Measurement <i>Frequency Range</i> <i>0.15 MHz to 30 MHz</i> <i>0 dBµV to 137 dBµV</i>	EN55022:2006 EN55022:2006 +A1:2008 CISPR 22 (1997/2006/2008) CISPR 16 -2-1:2008 CISPR 16 -2-1:2014
	1.2 Radiated Emissions <i>Frequency Range:</i> <i>30 MHz to 2.5GHz</i> <i>quite zone 2m x 2m x 2m</i> <i>2.5GHz to 6GHz</i> <i>quite zone 1.5m x 1.5m x 1.5m</i>	EN55011:2007 IS 6842 ( 1997) IS 6873 (part2) :1999 CISPR 32 (2015) CISPR 16 -2-3
	1.3 Disturbance power measurement  <i>(Absorbing clamp – 30 MHz to 300 MHz)</i>	EN55022:2006 EN55022:2006 +A1:2008 CISPR 22 (1997/2006/2008) CISPR 16 -2-3 IS 6842 ( 1997) IS 6873 (part2) :1999 EN55011:2007 CISPR 16 -2-2 CISPR 14 (1993) CISPR 14- 1(2005)
	1.4 Immunity to Electrostatic Discharge	IEC 61000-4-2 (1995) IEC 61000-4-2 (2008) EN 61000-4-2 (1995)
	1.5 Immunity to electromagnetic HF field  <i>Frequency Range:</i> <i>80 MHz to 6 GHz</i> <i>Field strength: upto 30 V/m</i>	IEC 61000-4-3 (2002' 2010) IEC 61000-4-3 (2006) EN 61000-4-3 (2002) IEC 801-3 (1984)
	1.6 Electrical fast transient burst test <i>0.5 kV to 4.0 kV</i>	IEC 61000-4-4 (1995/2004/2012)
	1.7 Surge Immunity Test <i>0.5 kV to 12 kV</i>	IEC 61000-4-5 (1995/2005/2014)



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<p><u>1.0 EMC Tests (Cont)</u></p> <p>1.8 Test of immunity to conducted disturbances, induced by radio frequency fields <i>Frequency range: 150 kHz to 80 MHz</i> <i>EMF: upto 10 V rms</i></p> <p>1.9 Immunity to power frequency magnetic fields of external origin</p> <p>1.10 Damped oscillatory wave immunity test</p> <p>1.11 Conducted Disturbance Induced Current 2 kHz to 150 kHz 1 A and 2 A</p> <p>1.12 Voltage dips and Interruptions Max Voltage : 270 V Time period : 6 ms to 6 min Max current : 2 A</p> <p>1.13 EMC Generic &amp; product specific standards. These are accredited to the extent that the basic standards are included above</p>	<p>IEC 61000-4-6 (1996/2006/2008)</p> <p>IEC 61000-4-8 (2001/2009) EN 61000-4-8 (2001)</p> <p>IEC 61000-4-12 (1995)</p> <p>CLC/TR/50579: 2012</p> <p>IEC 61000-4-11 : 2004</p> <p>IEC 60688 (2002,2012) IEC 60601- 1-2:2001 IEC 60601 -1:2001 IEC 61326 - 1:2005, 2012 IEC 61000- 6-1(2003) IEC 61000- 6-2(2005) IEC 61000- 6-2(2016) IEC 61000- 6-3(2006) IEC 61000- 6-4(2006) IEC 62055-31:2005 IEC 62052-21:2004 EN 55024:1998 EN 14236 (2007) BS EN 14236 (2007) EN 1359 (1999) Incorporating Amendment No. 1 EN 61000- 6-1 EN 61000- 6-2 CISPR 11(2004) BS EN 62052-21:2004 IS 12784 part 1 (1989)</p>



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<p><u>2.0 Climatic Tests</u></p> <p>2.1 Dry Heat Test <i>Ambient to +120 °C</i></p> <p>2.2 Cold Test / resistance to storage temperature range <i>Ambient to - 40 °C and + 60 °C</i></p> <p>2.3 Damp Heat Cyclic / resistance to external humidity test <i>Temperature + 20 °C to + 60 °C</i> <i>Relative Humidity 30 % to 95 %</i></p> <p>2.4 Resistance to salt spray</p> <p>2.5 Salt Mist</p>	<p>IEC 60068-2-2 (1994) IS9000(part3/Sec1to5) (1977)</p> <p>IEC 60068-2-1 (1994) IS9000 (part2/Sec1 to 4) (1997)</p> <p>IEC 60068-2-30 (1980) AMD1 (1985) IS9000 (part5/Sec 1 to 2) (1981)</p> <p>BS EN 1359:2017 EN 1359:2017 BSEN 1359:1999 Incorporating Amendment No. 1 EN 1359:1998 + Amendment No. 1 Clause 6.3.2.1.5 &amp; 6.3.2.2.2 ISO 7253:1984. BSEN ISO 7253:2001 And EN 14236:2007 Clause 6.3.2.5 &amp; 6.3.3.2 ISO 9227:2006 &amp; ISO 9227:2012</p> <p>IEC 62052-11 and IEC 60068-2-11:1981</p> <p>In house procedure TP-GASM-4.1 As above</p>



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<p><u>3.0 Mechanical Tests</u></p> <p>3.1 Vibration test <i>Sweep frequency: 10 Hz to 5 kHz</i> <i>Displacement: 20 mm p-p</i> <i>Capacity: 400 kgf</i></p> <p>3.2 Shock test <i>Peak acceleration: 50 g, Half sine pulse Time duration: 11 ms and 18 ms</i></p> <p>3.3 Protection against dust IP2X, IP5X without suction</p> <p>3.4 Protection against water IPX1, IPX2, IPX3 and IPX4, without suction.</p> <p>3.5 Glow wire test/Resistance to heat and fire</p> <p>3.6 Spring and Pendulum Hammer Test</p>	<p>IEC 60068-2-6 (1995) IS9000 (part 8) :1987</p> <p>IEC 60068-2-27 (1987) IS9000(part7/Sec 1 to 5) (1979)</p> <p>IEC 60529 (1989) IS/IEC 60529: 2013 IS 12063(1987)</p> <p>IEC Pub 695-2-1 (1980) IS:11000 (Part2/sec 1) (1984)</p> <p>IEC60068-2-75 (1997-05)</p>
	<p><u>4.0 High Voltage Tests</u></p> <p>4.1 AC Voltage test <i>1 kV to 6 kV</i></p> <p>4.2 Insulation Resistance Test <i>Up to 100 MΩ</i> <i>Test voltage 500V dc</i></p> <p>4.3 Impulse Voltage Test <i>0.5 kV to 12 kV</i></p>	<p>IS2071 (Part-1) :1974</p> <p>IEC 61000-4-5 (1995/2005/2014) IEC 60060-1 (1989) IEC 61180</p>



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Signalling equipment on low voltage electrical installations	<p><u>5.0 Signalling equipment</u></p> <p>5.1 Band in use condition 5.2 Output signal measurement 5.3 Limits of disturbance power 5.4 Conducted disturbance test 5.5 Allowed use of the sub band 5.6 Transmitter output voltage 5.7 Maximum output levels 5.8 Inadvertent operation 5.9 Marking 5.10 Radio Frequency Electromagnetic Field (Amplitude and pulse modulation) 5.11 Electrostatic Discharges 5.12 RF Common mode AM 5.13 Power frequency Magnetic field 5.14 Fast Transients and surges 5.15 Narrow band conducted interference</p>	<p>EN50065-1:2001 EN50065 -2-2: 2003 + A1:2005 EN50065 -2-3: 2003 +A1:2005 EN50065-2-1: 2003 + A1:2005</p>
<p>Power Quality Instruments (PQI)</p> <p>Class A and Class S</p> <p>Functional and uncertainty tests</p>	<p><u>6.0 Power Quality Instruments (PQI)</u></p> <p>6.1 Power Frequency 6.2 Magnitude of the Supply Voltage 6.3 Flicker 6.4 Supply voltage dips and Swells 6.5 Supply voltage interruption 6.6 Supply voltage unbalance 6.7 Voltage Harmonic 6.8 Voltage Inter-harmonic 6.9 Mains Signalling Voltage 6.10 Under/over deviation 6.11 Rapid Voltage Changes 6.12 Current magnitude 6.13 Current harmonics 6.14 Current inter harmonics 6.15 Current unbalance 6.16 Flagging 6.17 Clock uncertainty testing 6.18 Variations due to external influence quantities 6.19 Mixed influence quantities 6.20 Fast transients 6.21 Transient voltages</p>	<p>IEC 61000-4-30 Ed 3.0 2015-02 IEC61000-4-30 Ed. 2.0 2008-10 IEC 62586-1 Ed.1.0 2013-12 IEC 62586-2 Ed.1.0 2013-12 IEC61000-4-15 Ed 2.0 2010-08 IEC61000-4-7 Ed 2.0 2002-08 IEC61000-2-4 Ed 2.0 2002-06 IEC 62586-1 Ed.2.0 2017-05 IEC62586-2 Ed.2.0 2017-03</p>



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
<p>The following tests are paragraph by paragraph from the relevant meter standards and demonstrate the comprehensive nature of the accreditation. In the main the test methods are covered in the basic standards in the previous sections.</p>		
<p>Static Watthour and VAR hour meters, including prepayment meters and smart meters</p>	<ol style="list-style-type: none"> <li>1. AC Voltage test <i>1 kV to 6 kV</i></li> <li>2. Insulation Resistance Test <i>Up to 100 MΩ</i> <i>Test Voltage: 500 V dc</i></li> <li>3. Impulse Voltage Test <i>0.5 kV to 12 kV</i></li> <li>4. Limits of Errors</li> <li>5. Meter Constant</li> <li>6. Starting Conditions</li> <li>7. Ambient Temperature Influence</li> <li>8. Repeatability of errors test</li> <li>9. Test of power consumption <i>(Upper limits are 100 VA for the current circuit and 10W or 50 VA for the voltage circuit )</i></li> <li>10. Influence of Self Heating</li> <li>11. Influence of Heating</li> <li>12. Immunity to Earth Fault</li> <li>13. Test/abnormal voltage condition For test 4 to 13 <i>Single Phase: 0.04 W to 38.4kW</i> <i>Three Phase: 0.12 W to 115.2kW</i> <i>30 V to 320 V</i> <i>1 mA to 240 A</i></li> <li>14. Start Up Test of energy meters <i>30 V to 320 V</i></li> <li>15. No load condition <i>30 V to 320 V</i></li> </ol>	<p>IS13779 AMD 5 (MARCH 2015) IS14697 AMD 4 (DEC 2014) IS15884:2010 IS 11000 part I &amp; II (1984) IS 16444:2015 IS16444: Part 1(2015)+A1: 2017 IS16444: Part 2: 2017 IEC 61268 (1995) IEC62052 11 (2003) + A1:2016 IEC62053-21 (2003) + A1:2016 IEC62053- 22 (2003) + A1:2016 IEC 61000-4-5(1995) IEC 61000-4-5(2014) IEC 60060-1 (1989) IEC 61000-4-5 (2005) IEC62053-23(2003) + A1:2016 IEC 61268 (1995) IEC 62053-61: 1998 IEC62052-21:2004 IEC 60601-1-2: 2001 IEC62055- 31:2005 IEC62053- 23 (2003) IEC 60687 (1992) IEC 60687 (1993) IEC 61036 (2000) IEC 61036 (1997) IEC 60695-2-10(2000) IEC 60695-2-11(2000) IEC 60529 (1989) IEC 60529 (1989) IS 12063(1987) IEC 62059-32-1:2011 IEC 62053-24 (2014) + A1:2016 IEC 62053-31 (2015) SPM1618 BS EN 62053 -21:2003 AS 62053.22 (2005) BS EN 62053 -22:2003 BS EN 62053 -23:2003 BS EN 60687:1993 BS EN 61036:1997 BS EN 62052- 11:2003 BS EN 62052- 21:2004 BS EN 62054- 21:2004 IEC 60068-2-30 AMD1(1985)</p>



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Static Watthour and VAR hour meters, including prepayment meters and smart meters (cont'd)	<p>16. Short time over voltage test</p> <p>17. Spring and pendulum hammer tests <i>0.20 Nm, 0.22 Nm, 0.35 Nm, 0.50 Nm, 0.70 Nm, 1.00 Nm</i></p> <p>18. Resistance to heat and fire <i>Up to 1000 °C</i></p> <p>19. Tests of effect of voltage dips and short interruptions / influence of supply voltage <i>At 63.5 V, 110 V and 240 V; 50Hz</i></p> <p>20. Interpretation of test results and adjustments</p> <p>21. Test of influence quantities (a)Voltage variation, (b)Frequency Variation, (c)Reverse phase sequence, (d)Voltage unbalance, (e)Auxiliary voltage, (f)Harmonic components in current and voltage circuits, (g)10 percent of third harmonics, (h)Sub-harmonics in a.c. circuit (i)Continuous magnetic induction of external origin, (j)Continuous abnormal magnetic induction of external origin (k)Magnetic induction of external origin,(l)DC and even harmonics in AC circuit, (m)Odd harmonies in AC circuit, (n)Operation of accessories (o)Abnormal AC magnetic induction of external origin (<i>10mT, 200mT</i>) <i>Single Phase: 0.04 W to 38.4 kW Three Phase: 0.12 W to 115.2 kW</i></p> <p>22. Short time over current test <i>20 A to 7000 A</i> <i>(1/2 cycle to 50 cycles)</i> <i>(1/2 cycle up to 12 kA peak)</i></p> <p>23. Short time over current test <i>up to 1000 A for up to 25 cycles and up to 7000 A (½ cycles)</i></p>	<p>IS9000 (part 5/Sec 1 to 2) (1981) AS 62053.23(2006) AS 62052-21:2006 AS 62052.11 (2005) AS1284.5 (2000) AS1284.9 (1993) AS 62053-22 (2005) AS 62054.21 (2006) AS 62053.21 (2005)</p> <p>EN50470 -1:2006 EN50470 -3:2006 EN60068-2-75(1997)</p> <p>NMI M6 (2010), NMI M6 (2012) CBIP- 88 (February 2002)</p> <p>CBIP,Publication No.304 CBIP,Publication No.325 (Jan 2015)</p> <p>OIMLR46-1/-2 Ed 2012 IEC 61000-4-11 :2004</p>





2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Static Watthour and VAR hour meters, including prepayment meters and smart meters (cont'd)	<p>24. Surge Immunity Test <i>0.5 kV to 12 kV</i></p> <p>25. Electrical fast transient burst test <i>0.5 kV to 4.0 kV</i></p> <p>26. General and constructional / Mechanical requirements (A)General: (a)Meter case (b)Display of measured values (c)Output device Optical output device characteristics. Irradiance and pulse parameters (d)Window (B)Terminal: (a)Terminal block(s) - Protective earth terminal, including heat deflection test (b)Terminal cover(s) (c)Clearance and Creepage distances (d)Insulating encased meter of protective class II (e)Marking of meters</p> <p>27. Conducted Radio Interference Emissions Measurement <i>Frequency Range</i> <i>0.15 MHz to 30 MHz</i> <i>0 to 137 dB<math>\mu</math>V</i></p> <p>28. Test of immunity to conducted disturbances, induced by radio frequency fields <i>Frequency range 150 kHz to 80 MHz, EMF: 10 V rms</i></p> <p>29. Immunity to electromagnetic HF field <i>Frequency Range: 80 MHz to 3GHz</i> <i>Field strength: 30 V/m</i></p> <p>30. Radiated Emissions Measurement <i>Frequency Range: 30 MHz to 6GHz</i> <i>Range: 0 to 137 dB<math>\mu</math>V</i></p>	<p><b>As listed on pages 7 &amp; 8</b></p>



2437

Accredited to  
ISO/IEC 17025:2017

### Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Static Watthour and VAR hour meters, including prepayment meters and smart meters (cont'd)	31. Damped oscillatory wave immunity test 32. Immunity to Electrostatic Discharge 33. Immunity to power frequency magnetic fields of external origin 34. Dry Heat Test <i>Ambient to +120 °C</i> 35. Cold Test <i>Ambient to - 40 °C</i> 36. Damp Heat Cyclic test <i>Temperature + 20 °C to + 70 °C</i> <i>Relative Humidity 30 % to 98 %</i> 37. Operation within the specified operation range 38. Operation within the limit range of operation 39. Storage and transport outside the limit range of operation 40. load switching capability 41. Token carrier interface 42. Vibration test <i>Sweep frequency: 10 Hz to 3 kHz</i> <i>Displacement: 20 mm p-p</i> <i>Capacity 400 kgf</i> 43. Protection against dust and water <i>IPX1, IPX2, IPX3, IPX4 and IP5X without suction.</i> 44. Shock test <i>Peak acceleration: 50 g</i> <i>Half sine pulse</i> <i>Time duration: 11 ms and 18 ms</i>	<b>As listed on pages 7 &amp; 8</b>



2437

Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Yadav Measurements Private Limited**

**Issue No: 030 Issue date: 03 July 2019**

**Testing performed at main address only**

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Static Watt hour and VAR hour meters, including prepayment meters and smart meters (cont'd)	45. Requirement of time keeping 46. Test of keeping time 47. Test of consumption based charging functions 48. Test of time-based charging functions 49. Functional requirements (a)General (b)Robustness of meter accounting process 50. Stability of meteorological Characteristics by applying elevated temperature. 51. High order Harmonics (Test of influence)	<b>As listed on pages 7 &amp; 8</b>
Particular requirement for time switches (synchronized & crystal controlled)	1. Variation of the supply frequency 45 Hz to 65Hz Single phase: 0.04 W to 38.4 kW) Three Phase: 0.12 W to 115.2 kW) 2. Immunity to DC magnetic fields 1000 AT, 67 mT to 0.27 T 3. Immunity to AC magnetic fields 0.5 mT 4. Voltage dips and short interruptions 6 ms to 6 min 5. Tests of effects of supply interruptions on synchronous time switches Voltage 270 V <sub>p-n</sub> 6. Long interruptions of supply voltage Time up to 6 hours Voltage up to 320 V <sub>p-n</sub>	AS62052-21:2006 AS 62054.21(2006) IEC 61000-4-11 :2004



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Particular requirement for time switches (synchronized & crystal controlled) (cont'd)	<p>7. Operation reserves <i>Time up to 36 hours</i> <i>Voltage up to 320 V<sub>p-n</sub></i></p> <p>8. Backup power supply replacement Time &lt; 5 minutes</p> <p>9. Functional requirements and test accuracy <i>(a) time setting and programming</i> <i>(b) time switches with mechanical analogic dials</i> <i>(c) time switches with digital displays</i></p> <p>10. Time keeping accuracy <i>Time up to 30 days</i> <i>Voltage up to 320 V<sub>p-n</sub></i></p> <p>11. Requirement for synchronous time and crystal switches - test of time keeping accuracy <i>(a) test of synchronous and crystal controlled time switches</i> <i>(b) test of synchronous and crystal controlled time switches on operation reserve</i></p> <p>12. Test of time keeping accuracy of crystal-controlled time switches with temperature <i>Frequency: 45 Hz to 65 Hz</i> <i>Single phase: 0.04 W to 38.4 kW</i> <i>Three Phase: 0.12 W to 115.2 kW</i> <i>Temperature -10 °C to + 40 °C</i></p> <p>13. Switching accuracy <i>time up to 168 hours</i> <i>(a) test on time switches with dials</i> <i>(b) test on time switches with digital displays</i> <i>(c) synchronization (time up to 1 minute)</i></p> <p>14. Test of influence of harmonics <i>Single phase: 0.04 W to 38.4 kW</i> <i>Three Phase: 0.12 W to 115.2 kW</i> <i>Time up to 30 days</i></p>	AS 62052-21:2006 AS 62054.21(2006) (cont'd)



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Tariff and load control equipment	<ol style="list-style-type: none"> <li>1. Electrical requirements and tests</li> <li>2. Supply frequency range</li> <li>3. Output elements</li> </ol>	AS62052-21:2006 EN 62059-32-1:2012
Measuring Instruments - Electrical measuring transducers	<ol style="list-style-type: none"> <li>1. Environmental condition test</li> <li>2. Variations due to Auxiliary Supply Voltage</li> <li>3. Variations due to Auxiliary Supply frequency</li> <li>4. Variations due to Ambient Temperature</li> <li>5. Variations due to the frequency of the input quantities</li> <li>6. Variations due to input Voltage</li> <li>7. Variations due to input Current</li> <li>8. Variations due to power factor</li> <li>9. Variations due to output load</li> <li>10. Variations due to distortion of the input quantities</li> <li>11. Variation due to magnetic fields of external origin</li> <li>12. Variation due to unbalanced currents</li> <li>13. Variation due to the interaction between measuring elements</li> <li>14. Variation due to self-heating</li> <li>15. Variation due to continuous operation</li> <li>16. Permissible excessive inputs</li> <li>17. Continuous excessive inputs</li> <li>18. Excessive inputs of short duration</li> <li>19. Variation due to common mode interference</li> <li>20. Variation due to series mode interference</li> <li>21. Test of limits of Intrinsic Error</li> <li>22. Marking</li> <li>23. Drop and Topple Test</li> <li>24. Test for temperature rise</li> <li>25. Limiting condition for storage and transport (up to 80 °C)</li> </ol>	IEC 60068-2-3 (1985) IEC 60688 (2002) IEC 60688 (2015) IS 12784 part 1 (1989) IEC 60521 (1988) IEC 61000-4-12 (1995) IEC 61010-1(2001)



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Measuring Instruments - Electrical measuring transducers (cont'd)	26. Response time ( <i>up to 700 ms</i> ) 27. Limiting value of output ( <i>0 V to 320 V, 0 A to 120 A</i> )  28. Sealing verification 29. Ripple content of output ( <i>0 V to 320 V, 0 A to 120 A</i> ) 30. Over range of measurand ( <i>0 V to 320 V, 0 A to 120 A</i> ) and other safety requirements 31. Impulse voltage tests 32. High frequency disturbance test 33. Voltage test, insulation tests	As listed on previous page
Electricity Metering Equipment (AC)	Information and marking requirements ( clause 5) General. Labels, signs and signals. Information for selection. Information for installation and commissioning. Information for use. Information for maintenance.  Protection against electrical shock (clause 6) General requirements Determination of accessible parts. Limit values for accessible parts. Primary means of protection (protection against direct contact). Additional means of protection in case of single fault conditions (protection against indirect contact). Connection to external circuits. Insulation requirements. Insulation requirements between circuits and parts. Constructional requirements for protection against electric shock.  Safety related electrical tests.	IEC 62052-31:2015 AS 62052-31:2017 Clause 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 Annex A to K



2437

Accredited to  
ISO/IEC 17025:2017

### Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Electricity Metering Equipment (AC) (cont'd)	<p>Protection against mechanical hazards (7) General. Sharp edges. Provisions for lifting and carrying. Resistance to mechanical stresses (8) General. Spring hammer test.</p> <p>Protection against spread of fire (9) General. Eliminating or reducing the sources of ignition within the equipment. Containment of fire within the equipment, should it occur. Limited-energy circuit. Overcurrent protection</p> <p>Equipment temperature limits and resistance to heat (10) Surface temperature limits for protection against burns. Temperature rise limits for terminals. Temperature of internal parts. Temperature test. Resistance to heat.</p> <p>Protection against penetration of dust and water (11) Protection against liberated gases and substances explosion and implosion - Batteries and battery charging (12)</p> <p>Components and sub-assemblies (13) General. Mains transformers tested outside equipment. Printed wiring boards. Components bridging insulation. Circuits or components used as transient overvoltage limiting devices.</p>	IEC 62052-31:2015 AS 62052-31:2017 Clause 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 Annex A to K



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<p>Hazards resulting from application - Reasonably foreseeable misuse (14) Risk Assessment (15)</p> <p>Measuring circuits for touch Current (Annex A) Examples for insulation between Parts (Annex B) Examples for direct connected meters equipped with supply control and load control switches (Annex C) Test circuit diagram for the test of long term overvoltage withstand (Annex D) Test circuit diagram for short current test on the current circuit of direct connected meters (Annex E)</p> <p>Examples for voltage tests (Annex F) Additional a.c. voltage tests for electromechanical meters (Annex G) Test equipment for cable flexion and pull test (Annex H) Routine tests (Annex I) Examples of battery protection (Annex J) Rationale for specifying overvoltage category III (Annex K)</p>	
<p>Diaphragm and Ultrasonic domestic gas meters</p>	<p><b>Metrological performance:</b> Permissible errors of indication Carried out on air only from 0.016 m<sup>3</sup>/hour to 6.6 m<sup>3</sup>/hour</p> <p>Error on gas Gas-air relationship Temperature sensitivity Pressure absorption Starting flow rate Metrological stability Influence of other devices Cyclic volume Installation effects Zero flow</p>	<p>In house procedure TP-GASM-P-1.1</p> <p>BS EN 1359:2017 EN 1359:2017</p> <p>BS EN 1359:1999 Incorporating Amendment No. 1 EN 1359:1998 + Amendment No. 1 clause 5, clause 7.1.3 and B.2.3</p> <p>EN 14236:2007 and BSEN 14236 (2007) clause 5,7.3 and annex C</p>





2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	Reverse flow Low flow registration High flow registration Overload flow rate Mode comparison Pulsed (unsteady) flow Environment and humidity Immunity to contaminants in gas stream Meters with gas temperature conversion devices	EN 16314:2013 and BSEN 16314:2013, Clause 4.11.1, 7.13.4.4, 7.13.4.9
Diaphragm and Ultrasonic domestic gas meters	<b>Construction and material properties</b> General Robustness of meter case including: Protection against penetration of dust and water Resistance to internal Pressure External leak tightness Heat resistance Connections Resistance to vibration Resistance to Impact Resistance to mishandling Corrosion protection Casework decorative finish Ageing of non-metallic casework Ageing of external surfaces of the meter Resistance to external humidity Flame retardance of external surfaces Resistance to the effects of toluene/iso-octane vapour Resistance to water vapour Ageing Meter case sealing test Connections Orientation Threads Strength Torque Bending moment Protective coatings Scratch resistance Adhesion Impact resistance Resistance to humidity	In house procedure TP-GASM-P-2.1  BS EN 1359:2017 EN 1359:2017 BSEN 1359:1999 Incorporating Amendment No. 1 EN 1359:1998 + Amendment No. 1 clauses 6  EN 14236:2007 and BSEN 14236 (2007) clause 6  excluding 6.7 Protection against solar radiation  EN 16314:2013 and BSEN 16314:2013 Clause 4.8, 4.9.5, 4.9.6, 4.10, 4.14, 4.15, 4.16, 7.13.4.7, Annex – D3, D5, 7.13.4.6.3, Annex – D3, D4



2437  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Yadav Measurements Private Limited**  
**Issue No: 030 Issue date: 03 July 2019**

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	Resistance to storage temperature range Pressure measuring point Insulation feet Resistance to high ambient temperature Magnetic index drive Reverse flow devices	
Diaphragm and Ultrasonic domestic gas meters	Optional features Pressure measuring point Resistance to high ambient Temperatures Meter fitted with a thermal shut-off valve Ancillary devices  Index Markings Software Battery  Immunity to electromagnetic fields Electrostatic discharge Radio frequency electromagnetic field Electromagnetic induction (power frequency and pulsed field) Radio Interference suppression Permanent magnetic fields	EN 14236:2007 and BSEN 14236 (2007) clauses 7, 8, 9, 10, 12, 13 Excluding clauses 7.5, 9.3.2.2  EN 16314:2013 and BSEN 16314:2013 Clause 4.12.2, 4.12.3, 4.12.4, 4.12.5, 4.12.6, 4.12.7
Diaphragm domestic gas meters	<b>Mechanical performance</b> Meter assembly Index Diaphragm and other components	BS EN 1359:2017 EN 1359:2017 BSEN 1359:1999 Incorporating Amendment No. 1 EN 1359:1998 + Amendment No. 1 clause 7
Diaphragm domestic gas meters	<b>Markings</b>	BS EN 1359:2017 clause 8 EN 1359:2017 clause 8 EN 1359:1999 clause 8
Diaphragm and Ultrasonic domestic gas meters	<b>Additional functionality</b> Types of additional functionality devices AFD1, AFD2, AFD3 Climatic environments Closed location Safety requirements	In house procedure TP-GASM-P-3.1  EN 16314:2013 and BSEN 16314:2013 Clause 4.4, 4.5, 4.9.1,



2437

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Yadav Measurements Private Limited

Issue No: 030 Issue date: 03 July 2019

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	Expected lifetime Security Power system Display Diagnostics Metrological influence AFD connections Input to AFD & Output from AFD Data storage Time interval accuracy Energy Calculation within the meter/AFD Tariffs Display/Human interface Gas valve and System Design Quality Valve operation & performance Display of valve related information Valve closing & opening Endurance Registers Prepayment System with valve and without a valve History of Consumption Memory Access profiles Non-volatile memory Valve performance Opening and Closing Water vapour Endurance Documentation Ageing Marking	4.9.2, 4.11, 4.17, 5, 6, 7, 8, 9, Annex D2, D4, D5
END		